



Features

Powered by DynamicLux™ Technology

Dimming: Supports market available SCR dimmers that support incandescent bulbs (e.g. Leviton, Lutron)

Long Lasting: 25,000 hrs

On/Off: Unlimited switching, no negative effects on lifetime

Sensors & Timers: Will not reduce lifetime

Energy Savings: Up to 80% savings over standard incandescent bulbs

Warranty: 3 year limited warranty

Cold Cathode Fluorescent Lamp


Specifications

GL108D/120F	
Part Number	FSJKDTBT0601
Product Series	Globe
Voltage	AC 110-120V 60Hz
Watt	8W
Lumen Output	360 lm
Lifetime	25,000hr
Luminous Efficacy	45 lm/W
Color Temperature	Warm White (2700K) ¹
Lamp Base	Medium Screw (E26)
Color Rendering Index	≥ 80
Dimming	100% to 10% ²

Dry locations only

¹ Also available in other color temperatures with different performance

² Dimming range is measured in lux level, may perform differently with different dimmers



Dimensions

GL108D/120F	
MOL (a)	5.12 in
Diameter (b)	Ø1.77 in
Max Width (c)	Ø2.95 in
Weight	3.81 oz
Standard Pack	50pcs / box

DynamicLux™ Technology

Proprietary Cold Cathode Fluorescent Lamp (CCFL) technology powered by DynamicLux™ that enables CCFL with high wattage for general lighting applications. It features smooth dimming with unlimited and intensive on/off switching. It also provides longer lifetime and more energy savings when integrated with sensors.



Imported By:



Tel: (201) 965-4899
 Fax: (201) 935-1748
 www.NuLiteTechnologies.com
 info@NuLiteTechnologies.com
 30 Park Avenue
 Lyndhurst, NJ 07071